

• **SUPER
ADVERTISING
BARRIER GATE**

AKD139 II



Function & Feature

- Sleek, durable outdoor design with advanced surface treatment; ambient light and waterproof LED light strip (photosensitive control) add luxury and intelligence.
- Middle-lifting barrier arm (no left/right distinction) with customizable length (max. 8m with pull rod); rectangular vertical bars with 120mm spacing.
- 24V brushless motor and DC servo control for high efficiency, adjustable speed, and stable operation.
- Multiple safety protections: obstacle rebound, ground sensor anti-crushing, and anti-crushing rubber strip to prevent damage.
- Automatic functions with optional vehicle detector: auto-lowering after vehicle passage, auto-lifting if a vehicle is detected during lowering.
- Open-priority function: immediate lifting when an open signal is received during lowering.
- Various control methods: external control box, remote control for flexible operation.
- Standard electrical interfaces for easy integration with other systems.
- Optional backup power system to solve power outage issues.
- Equipped with "auto-close" and comprehensive anti-crushing features for enhanced safety.

Technical Parameter

Power supply	AC220V±10%
Driver	24V BLDC Motor
Motor power consumption	250W
Max arm length	6M
Speed	8s
Housing dimension	560*650*1650mm
Boom height from ground	1498mm
LED Light	DC12V
Remote-control distance	≤30m
Protection grade	IP54
Working Temperature	-30° to 80°
Cabinet Weight	170kg
Boom weight	69kg

