

Parking Payment Kiosk Configuration (Model KMY8208G-19)			
No.	Module	Model / Brand	Technical Specifications
1	Main Control Module	Designated	Requires 8 serial ports and 6 or more USB ports.
2	Host Chassis + Power Supply	Designated	
3	Capacitive Touch All-in-One Display	Hesheng Gaoke	19-inch screen, 4:3 standard ratio, 6ms response time, 260 nits brightness, 700:1 contrast ratio, viewing angle 130° horizontal / 110° vertical
4	Banknote Acceptor Module	ITL-NV9	Banknote capacity 600 notes (recognizes Saudi Arabian currency)
5	Banknote Dispenser Module	ITC-NDE1000	Banknote capacity 800 notes (one module supports one denomination)
6	POS 3-in-1 Card Reader	Designated	Reserved position with cover plate (model specified by customer)
7	Barcode Scanner	Dewo	Accurate recognition of 1D and 2D barcodes
8	Intercom System		Intercom + microphone + help-call function
9	Network Splitter		4-port network expansion
10	Printer Module 1	CASHINO	KP-301H, 80mm thermal receipt printer
11	Printer Module 2	CASHINO	KP-301H, 80mm thermal receipt printer
12	Coin Acceptor Module	G13	Accepts Kazakhstani coins
13	Coin Dispenser Module	MK2	Dispenses one coin denomination
14	Alarm Module	KMY-XL128	Access controller + control board + sensor + alarm
15	Contactless Card Reader Module		Customer supplied
16	LED Light Strip		Blue light strip, always on + control board
17	Combined Power Supply Module	Xinxing	Supplies 12V / 24V power to banknote unit, printer, coin unit, etc.
18	Audio System	Mini Speakers	One on each side, effective output 25W.
19	Cooling System		4 fans with dust filters
20	Coded Cash Box		In-house manufactured by KMY + combination lock
21	UPS Power Module	EAST	1000VA, USB interface, with program control
22	Complete Cabinet (outdoor powder coating)	KMY8208G-17	Lobby-style structure with hot-rolled steel plate exterior. Housing thickness: 1.5-2.0mm. Appearance: novel, elegant and premium; Material: rigid and thick, resistant to deformation; Internal structure: modular maintenance design, simple and convenient servicing; Neat and standardized wiring. Includes safe box. Cabinet uses universal-key top-and-bottom lock design.
23	Cabinet Multi-point Interlocking Lock	Mechanical multi-point	Multi-point lock for the complete cabinet
24	Auxiliary Materials	Circuit breaker, power strip, power cables, data cables, etc.	
25	Communication	TCP/IP	
Packaging (S2)		Three-layer packaging for the complete unit (eco-friendly wooden crate)	
Transportation & Insurance (S3)		Within Shenzhen (Party A's company location)	
Warranty & Costs (S6)		One-year free warranty for OEM parts, excluding on-site service.	

Machine appearance rendering as below:

产品型号: KMY8208G-19

